



HM

Measuring Wheel Encoder



Electrical 電氣規格

Detection System 編碼器類型	Incremental 增量型
Power Source 電源電壓	DC 8 ~ 24V
Current Consumption 消耗電流	40 mA or below
Response Frequency 響應頻率	20 KHz
Output Voltage 輸出電壓	VoH: Vcc - 0.7V, VoL: 0.5V
Output Phase 輸出相位	A A, B
Output Wave Form 輸出波形	
Output Mode 輸出型態	Voltage

Connection 接線方式

Red	Black	White
+	-	A
Green	Shield	
B		

Wheel Circle Length 輪周長

Meter Wheel 米輪	0.3 Meter ± 0.1%
Yard Wheel 碼輪	0.3 Yard ± 0.1%

Application 應用

- Length Measuring For Industry Machine
產業機器長度量測

Feature 特點

- Wheel Measuring Sensor 碼輪型傳感器
- Mounting Easy 安裝容易
- Meter、Yard Wheel Available
米、碼輪可選用

Resolution 解析度

Type T 型號	Resolution (Meter or Yard) 輸出單位 (可選用米、碼輪)	Output Signal 輸出信號
HM-AB2	0.1	Bi-Direction 雙向使用
HM-AB4	0.001	

Mechanical Spec. 機械規格

Max. Measuring Speed. 最大速度	360 M/min
Net Weight. 淨重	500g

Environmental Spec. 環境條件

Operating Temp. 操作溫度	-10 ~ +70°C
Storage Temp. 保存溫度	-20 ~ +80°C
Operating Humidity 操作溼度	RH 85% max non-collecting
Shock 衝擊	490 m/s ² , 3Dx2 times
Vibration 震動	0.6mm, 10~55KHz, 3Dx30min.
Protection 防護等級	IP 54



HM

Measuring Wheel Encoder

Ordering Information 訂購資訊

HM - - 0 5 0

解析度

AB2: 0.1Meter
AB4: 0.001Meter

單位

M: Meter
Y: Yard
: none

線材樣式

C: cable 電纜線

Mechanical Drawing 外型尺寸

Unit: mm

